

PATENT ABSTRACTS OF JAPAN

(11)Publication number:

11-202802

(43) Date of publication of application: 30.07.1999

(51)Int.CI.

G09F 9/37

(21)Application number : 10-005729

(71)Applicant : CANON INC

(22)Date of filing:

14.01.1998


PROBLEM TO BE SOLVED: To maintain a display state

(72)Inventor: IKEDA TSUTOMU

(54) DISPLAY DEVICE

(57)Abstract:

without applying a voltage to electrodes continuously and to reduce the power consumption by fixing both the ends of a conductive film to a 1st and a 2nd substrate respectively at diagonal positions of a cell and fixing the conductive film so that it slackens in the cell. SOLUTION: Both the ends of the conductive colored film 5 are adhered directly or closely to the 1st substrate 1 and 2nd substrate 2 and arranged in an S shape in a section. On the 1st substrate 1 and 2nd substrate 2, a 1st electrode 6 and a 2nd electrode 7 are formed. When the voltage is applied so that the 1st electrode is a negative electrode and the conductive colored film 5 is a positive electrode, the majority of the S-shaped conductive colored film 5 comes into contact with the top of the 1st electrode 6 (a). When the voltage is so applied that the 2nd electrode 7 is a negative electrode and the conductive colored film 5 is a positive electrode, the majority of the S-shaped conductive colored film 5



comes into contact with the top of the 2nd electrode 7 (b). Namely, the conductive colored film 5 move in the opposite directions.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration] [Date of final disposal for application]

[Patent number]
[Date of registration]
[Number of appeal against examiner's decision of rejection]
[Date of requesting appeal against examiner's decision of rejection]
[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office